



Size Data, Load Data and Standards

TYRE SIZE	RIM	WEIGHT	SHIPPING VOLUME	ETRTO STANDARDS						
				TYRE DIMENSIONS		LOAD CAPACITY kg				
				MAX: OVERALL WIDTH	OVERALL DIAMETER (2%)	COUNTER BALANCED LIFT TRUCKS		OTHER VEHICLES UP TO		
						UP TO 25 km/h		25 km/h	10km/h	6 km/h
mm	mm	LOAD WHEELS	STEERING WHEELS							
400-8 w*	3.00D-8	10,5	0,014	104	406	950	730	730	860	950
400-8	3.00D-8	11,0	0,016	115	406	950	730	730	860	950
500-8	3.00D-8	17,0	0,023	136	458	1415	1090	1090	1285	1415
15*4 1/2-8	3.00 - 8	9,5	0,014	118	377	1040	800	800	945	1040
16*6-8	4.33R-8	16,0	0,021	151	417	1270	975	975	1150	1270
18*7-8	4.33R-8	20,5	0,027	164	453	2145	1650	1650	1945	2145
6.00-9	4.00E-09	27,5	0,036	163	529	1885	1450	1450	1710	1885
21*8-9	6.00E-09	34,0	0,041	184	524	2755	2120	2120	2500	2755
6.50-10	5.00F-10	35,5	0,048	179	576	2340	1800	1800	2125	2340
200/50-10	6.5-10	23,0	0,031	188	458	2470	1900	1900	2240	2470
23*9-10	6.50E-10	51,0	0,066	233	583	3160	2430	2430	2865	3160
7.00-12	5.00S-12	46,5	0,061	178	657	2920	2240	2240	2645	2920
27*10-12	8.00G-12	76,0	0,090	242	676	3900	3000	3000	3540	3900
28*9-15**	7.0-15	57,0	0,085	230	693	3445	2650	2650	3125	3445
250-15	7.0-15	70,0	0,094	224	720	4545	3650	3650	4310	4545
250-15	7.5-15	70,5	0,094	224	720	4545	3650	3650	4310	4545
355/65-15	9.75-15	131,5	0,160	300	823	7800	6000	5450	6430	7000
8.25-15	6.5-15	92,5	0,120	222	819	4750	3650	3650	4300	4750
300-15	8.0-15	124,0	0,150	263	823	5850	4500	4500	5310	5850
10.00-20	7.0-20	169,0	0,240	287	1029	6000	5000			
	7.5-20	170,0	0,240	287	1029	6000	5000			
	8.0-20	171,0	0,240	287	1029	6000	5000			

** 28x9-15 – 815-15
 ** 700 – 15 (5.5) Available

